

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Vinyl Stair Nosings


1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarkettna.com


1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Vinyl Stair Nosings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants Tarkett Vinyl Stair Nosings are designed for interior applications only and not recommended for commercial kitchen environments.


1.3.2. **Styles:**



SLN-XX-A: Double Undercut Carpet Vinyl Stair Nosing, 3/4" (2.0 cm) tread depth, ~1-2/5" (3.6 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 1/4" (6.35 mm) carpet on step and riser.



SLN-XX-B: Double Undercut Carpet Vinyl Stair Nosing, ~2/3" (1.7 cm) tread depth, ~1-2/5" (3.6 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 1/4" (6.35 mm) carpet on step and riser.



SLN-XX-C: Double Undercut Carpet Vinyl Stair Nosing, ~3/5" (1.4 cm) tread depth, ~1-2/5" (3.6 cm) hinged square nose configuration, undercut for 3/8" (9.5 mm) to 3/8" (9.5 mm) carpet on step and riser.

1.3.3. **Physical Characteristics:** Lengths: 12 ft. (3.66 m), Packaging: 120 ft. (39.58 m) per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- **Meets ASTM F-2169** performance standards for Resilient Stair Treads, Type TV, Class 2
- **Abrasion Resistance:** ASTM D 3389, < 1.00 gram weight loss
- **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .6 for flat surfaces
- **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Stair Tread, Nosing, Riser, and Stringer installation instructions for complete details.

3.2. **Adhesives:**

- **Tarkett 946 Premium Contact Adhesive Coverage:**
 Non-porous Substrate:
 1 quart unit (0.95 liters) – 24 to 36 sq. ft.
 1 gallon unit (3.79 liters) – 144 to 215 sq. ft.
- **Tarkett 930 Two-part Epoxy Nose Caulk Coverage:**
 13.5 oz. cartridge, with #530 Caulking Gun at a 1/4" diameter bead – approximately 50 linear feet.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures can be implemented. Refer to vinyl nosing maintenance instructions for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
 Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project..

7. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 800.899.8916 Ext. 9297 Fax 440.632.5643
 info@tarkettna.com

www.tarkettna.com