

**1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1. **Proprietary Product:** Masquerade

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916  
 30000 Aurora Rd. (440) 543-8916  
 Solon, Ohio 44139  
 Web: www.tarketta.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Masquerade is manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861 Standard Specification for Resilient Wall Base, Type TP, and Group 1.

1.3.2. **Styles & Physical Characteristics:**

**Outline™** (MW-XXX-D): 5/16" (.313", 7.92mm) thick by 3-1/2" (8.89cm) height, 10 per carton, 8 ft lengths, 80 ft (24.4m) per carton, 47 lbs (21.3kg) per carton.

**Reveal™** 4-1/4" (MW-XXX-F): 1/4" (.25", 6.35mm) thick by 4-1/4" (10.8cm) height with a 45° angular top and a 7/32" (5.5mm) wide surface reveal, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 50 lbs (22.7kg) per carton.

**Silhouette™** (MW-XXX-J): 1/2" (.50", 12.7mm) thick and 4" (10.16cm) height, 6 per carton, 8 ft lengths, 48 ft (14.63m) per carton, 42 lbs (19.1kg) per carton

**Oblique™** (MW-XXX-N): 3/8" (.375", 9.53mm) thick by 3" (7.62cm) height with a 45° angular top, 7 per carton, 8 ft lengths, 56 ft (17.0m) per carton, 42 lbs (19.1kg) per carton.

**Classic™** (MW-XXX-Z): 3/8" (9.5 mm) thick by 5-1/4" (13.3 cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 54 lbs (kg) per carton.

**Traditional Wall Base:** (MB-XXX): Coved, 0.125" (3.17 mm) thickness, 4" (10.16 cm) height. Available in 4' (1.22 m) straight lengths and 120' (36.58 m) coiled lengths.

**QTR-XXX-A:** 1/2" (12.7 mm) wide by 1/2" (12.7 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 20 pieces per carton [160 ft. (48.8 m)]; weight of carton is 24 lbs (10.9 kg).

**QTR-XXX-D:** 3/4" (19.05 mm) wide by 3/4" (19.05 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 10 lengths [140 ft. (42.67 m)] per carton, weight of carton is 30 lbs (13.6 kg).

**SHU-XXX-A:** 1/4" (6.4 mm) wide by 1-1/2" (3.8 cm) high radius profile, 8 ft. (2.4 m) lengths with pressure sensitive adhesive backing, 10 pieces per carton [80 ft. (24.4 m) - 21 lbs. (9.5 kg)].

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

2.1. Products meet the following performance criteria for resistance to light, chemicals, and staining of adjacent materials when tested to the methods as described in ASTM F1861.

2.2. **Chemical resistance** (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution

2.3. **Resistance to light** (ASTM F 1515): ΔE < 8

2.4. **Fire Resistance:**

ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I  
 ASTM E84/NFPA 255 (Flame/smoke): Class C (Traditional)  
 ASTM E 84/NFPA 255 (Flame/Smoke) – Class B (All other profiles)

**3. INSTALLATION**

3.1. See Tarkett Masquerade installation instructions for complete details.

3.2. **Adhesives:**

**Tarkett 960 Cove Base Adhesive** (Porous surfaces):

Application: 1/8" x 1/8" x 1/8" square notched trowel

Approximate coverage (linear feet/gallon):

Outline:	230	to	280
Reveal:	185	to	235
Silhouette:	200	to	250
Oblique:	275	to	325
Classic:	145	to	195
Traditional:	200	to	250

**Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

1 Quart (0.95 liters)	–	24 to 36 sq. ft.
1 Gallon (3.79 liters)	–	100 to 150 sq. ft.

**4. AVAILABILITY AND COST**

Available through authorized Tarkett distributors nationwide.

**5. WARRANTY**

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**6. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.

**7. TECHNICAL SERVICES**

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.