### **CHOICE HOTELS**

COMFORT INN / SEA SCHEME







### **CHOICE HOTELS**

COMFORT INN / SEA SCHEME





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721 706.277.3000

Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

#### **Choose Tarkett Hospitality**

+ Approved Styles

+ Lowest Pricing + Broadloom Carpet

+ Fast Delivery + Lextron Solution-Dyed Nylon



Phone:

Product Type: Broadloom Guest Room Choice Item: SEA-CPT-001B Style Number: I332B Color Number: 248 Specs: 32 oz. - 12' Pattern Repeat: 18" x 24"



Product Type: Carpet Tile Guest Room Choice Item: SEA-CPT-002B Style Number: I337T Color Number: 428 Specs: 28 oz. Carpet Tile Size: 24" x 24"



Product Type: Broadloom Corridor Choice Item: SEA-CPT-010B Style Number: I336B Color Number: 536 Specs: 36 oz. - 12' Pattern Repeat: 72" x 126.86"



Product Type: Carpet Tile Corridor Choice Item: SEA-CPT-011B Style Number: I343T Color Number: 698 Specs: 36 oz. Carpet Tile Size: 24" x 24"



Product Type: Broadloom Lobby Choice Item: SEA-CPT-020B Style Number: I342B Color Number: 442 Specs: 36 oz. - 15' Pattern Repeat: 90" x 200"



Product Type: Broadloom BOH Choice Item: SEA-CPT-021 Style Number: 1334B Color Number: 792 Specs: 32 oz. - 12' and 15' Pattern Repeat: 36" x 36"

+ 10-Year Warranty



Product Type: LVT
Guest Room
Choice Item: SEA-LVT-001B
iD Latitude™
Style Number: PLWD
Color: 3605 Taos Oak
Specs: 6" x 48" Plank



Product Type: LVT
Public Space, All Areas
Choice Item: SEA-LVT-002B
iD Latitude™
Style Number: PLWD
Color: 3522 Créme Oak
Specs: 6" x 48" Plank

### **CHOICE HOTELS**

COMFORT INN / SEA SCHEME





Manufacturer: **Tarkett Hospitality** Address:

285 Kraft Drive Dalton, GA 30721

706.277.3000 Phone: Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

#### **Choose Tarkett Hospitality**

+ Approved Styles + 10-Year Warranty + Lowest Pricing + Broadloom Carpet

+ Fast Delivery + Lextron Solution-Dyed Nylon



Product Type: Resilient Wall Base Guest Room

Choice Item: SEA-RB-001 Millwork Reveal Wall Base Style Number: MW-32-F Color: 32 Pebble

Specs: .25" W x 4.25" H x 8' L



Product Type: Resilient Wall Base

Public Space, Corridor

Choice Item: SEA-RB-002 Millwork Reveal Wall Base Style Number: MW-TA5-F Color: TA5 Colonial Grey Specs: .25" W x 4.25" H x 8' L



Product Type: Resilient Wall Base

Public Space, Lobby


Choice Item: SEA-RB-003 Millwork Reveal Wall Base Style Number: MW-121-F Color: 121 Cement

Specs: .25" W x 4.25" H x 8' L



Product Type: Resilient Wall Base

Fitness Choice Item: SEARB-004 Millwork Reveal Wall Base Style Number: MW-199-F Color: 199 Dockside Specs: .25" W x 4.25" H x 8' L



Product Type: Threshold


Guest Room

Choice Item: SEA-TH-001

Thresholds

Style Number: VT-32-M2

Color: 32 Pebble Specs: 5.5" W x 3' L



Product Type: Threshold

Public Space

Choice Item: SEA-TH-004

Thresholds

Style Number: VT-32-M2 Color: 32 Pebble Specs: 5.5" W x 3' L



## SEA SCHEME BROADLOOM / GUEST ROOM





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: Guest Room
Choice Item: SEA-CPT-001B
Style Number: I332B Broadloom

 Color:
 248

 Width:
 12'

 Repeat:
 18" x 24"

Type: Dynamics - Multi Level Loop Servo Scroll Tip Shear

Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 32 oz. tufted face weight Primary Backing: Woven Polypropylene

Secondary Backing: Action Bac

Pile Height: .250" High, .187" Med, .062" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Broadloom

Flame Requirements: Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- · All Specifications subject to normal manufacturing tolerance.



# SEA SCHEME CARPET TILE / GUEST ROOM





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: Guest Room
Choice Item: CITY-CPT-002B
Style Number: 1337T Carpet Tile

Color: 428 Carpet Tile Size: 24" x 24"

Type: Dynamics – Servo-Scroll Loop Tip Shear Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 28 oz. tufted face weight Primary Backing: Woven Polypropylene


Secondary Backing: Ethos® Modular w/Omnicoat Technology
Pile Height: .337" High, .250" 1Med, .218" 2Med, .103" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Quarter Turn

Flame Requirements: Meets or exceeds requirement Class 1

- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104/CRI-105.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- · All Specifications subject to normal manufacturing tolerance.



BROADLOOM / CORRIDOR





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: Corridor
Choice Item: SEA-CPT-010B
Style Number: I336B Broadloom

Color: 536 Width: 12'

Repeat: 72" x 126.86"

Type: Intrepid – Multi-Level Loop Tip Shear
Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 36 oz. tufted face weight
Primary Backing: Woven Polypropylene
Secondary Backing: Unitary Action Bac

Pile Height: .250" High, .187" Med, .062" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Broadloom

Flame Requirements: Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- All Specifications subject to normal manufacturing tolerance.







Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: Corridor
Choice Item: SEA-CPT-011B
Style Number: I343T Carpet Tile

Color: 698 Carpet Tile Size: 24" x 24"

Type: Dynamics – Servo-Scroll Loop Tip Shear Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 36 oz. tufted face weight Primary Backing: Woven Polypropylene

Secondary Backing: Ethos® Modular w/Omnicoat Technology

Pile Height: .337" High, .218" Med, .125" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Quarter Turn

Flame Requirements: Meets or exceeds requirement Class 1

- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104/CRI-105.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- · All Specifications subject to normal manufacturing tolerance.



BROADLOOM / LOBBY





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: Lobby

Choice Item: SEA-CPT-020B
Style Number: I342B Broadloom

 Color:
 442

 Width:
 15'

 Repeat:
 90" x 200"

Type: Dynamics - Multi Level Loop Servo Scroll Tip Shear

Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 36 oz. tufted face weight Primary Backing: Woven Polypropylene Secondary Backing: Unitary Action Bac

Pile Height: .250" High, .187" Med, .062" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Broadloom

Flame Requirements: Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- · All Specifications subject to normal manufacturing tolerance.



BROADLOOM / BOH





Manufacturer: Tarkett Hospitality
Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Description: BOH

Choice Item: SEA-CPT-021
Style Number: I334B Broadloom

Color: 792 Width: 12' or 15' Repeat: 36" x 36"

Type: Dynamics - Multi Level Loop Servo Scroll Tip Shear

Content: Lextron Enviro-Green Solution Dyed Nylon

Weight: 32 oz. tufted face weight Primary Backing: Woven Polypropylene

Secondary Backing: Action Bac


Pile Height: .250" High, .187" Med, .062" Low

Gauge: 1/10"

Dye Method: Solution Dyed
Installation Method: Broadloom

Flame Requirements: Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- · All Specifications subject to normal manufacturing tolerance.



LVT / GUEST ROOM





Manufacturer: Tarkett Hospitality Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com

Standard

**Tarkett Value** 

Choice Item:

Classification: **ASTM 1700**  Class III, Type B (Solid Vinyl Floor) Techtonic®

6" x 48"

iD Latitude™

Wood 3605 Taos Oak

SEA-LVT-001B

Surface Treatment:

Size:

Total Thickness: 0.120" (3.05 mm) ASTM F386 Wear Layer Thickness: ASTM F410 20 mil (0.51mm) Installation Method: Glue-Down

Pattern: Pattern Type:

Color:

Format Type:

Plank Flexibility: ASTM F137 Pass Chemical Resistance: ASTM F925 Passes

Static Load Limit: ASTM F970 250 psi, ≤ 0.005" Heat Stability: **ASTM F1514** ΔE ≤ 8.0 Light Stability: ASTM F1515  $\Delta E \le 8.0$ SCOF ≥ 0.5 Slip resistance: **ASTM D2047** Squareness: ASTM F2055 Pass

Flammability: ASTM E648 Class 1 (≥ 0.45 W/cm<sup>2</sup>)

Residual Indentation: ASTM F1914

Commercial Warranty: 20-year limited

SureStart™ Underlayment 50003

Product Type Subflooring

Length 33.30 ft (10.1 m), 44.40 ft (13.5 m)

Total thickness 0.060" (1.5 mm) Width 3 ft, 4.50 ft

10 year limited light commercial Commercial Warranty

**†TECHTONIC® PROTECTION** 





### **SEA SCHEME** LVT / PUBLIC SPACE, ALL AREAS





Manufacturer: Tarkett Hospitality Address: 285 Kraft Drive

Dalton, GA 30721

Phone: 706.277.3000 Contact: Amber Osiecki

Amber.Osiecki@tarkett.com

Web: tarketthospitality.com **PROTECTION** 

**†TECHTONIC®** 



Standard **Tarkett Value** 

Choice Item: SEA-LVT-002B Classification: ASTM 1700

Class III, Type B (Solid Vinyl Floor) Techtonic®

Surface Treatment: Size:

6" x 48"

Total Thickness: ASTM F386 Wear Layer Thickness: ASTM F410

Installation Method:

0.120" (3.05 mm) 20 mil (0.51mm) Glue-Down iD Latitude™

Pattern: Pattern Type: Wood Color:

3522 Créme Oak

Format Type: Plank Flexibility: ASTM F137 Pass Chemical Resistance: ASTM F925 Passes

Static Load Limit: ASTM F970 250 psi, ≤ 0.005" Heat Stability: ASTM F1514 ΔE ≤ 8.0 Light Stability: ASTM F1515  $\Delta E \le 8.0$ SCOF ≥ 0.5 Slip resistance: **ASTM D2047** Squareness: ASTM F2055 Pass

Flammability: ASTM E648 Class 1 (≥ 0.45 W/cm<sup>2</sup>)

Residual Indentation: ASTM F1914

Commercial Warranty: 20-year limited