

CHOICE HOTELS





Manufacturer: Address: Phone:

Web:

Contact:

Tarkett Hospitality 285 Kraft Drive Dalton, GA 30721 706.277.3000 Amber Osiecki Amber.Osiecki@tarkett.com tarketthospitality.com

Choose Tarkett Hospitality

- + Approved Styles + Lowest Pricing
- + Fast Delivery
- + 10-Year Warranty
- + Broadloom Carpet
- + Lextron Solution-Dyed Nylon









Product Type: Broadloom Guest Room Choice Item: SUN-CPT-001C Style Number: I340B Color Number: 238 Specs: 32 oz. - 12' W Pattern Repeat: 48" x 48"

Product Type: Carpet Tile Guest Room Choice Item: SUN-CPT-002C Style Number: 1335T Color Number: 428 Specs: 28 oz. Carpet Tile Size: 24" x 24"

Product Type: Broadloom Corridor Choice Item: SUN-CPT-010C Style Number: 10936 Color Number: 992 Specs: 36 oz. - 12' W Pattern Repeat: 72" x 60" Side Match

Product Type: Broadloom BOH Choice Item: SUN-CPT-021 Style Number: 1334B Color Number: 792 Specs: 32 oz. - 12' and 15' Pattern Repeat: 36" x 36"





Product Type: LVT Guest Room Choice Item: SUN-LVT-001C ProGen™ Style Number: ProGen Color: 270266024 West Oak Drift Specs: 7" x 60" Plank

Product Type: LVT Public Space, All Areas Choice Item: SUN-LVT-002C iD Latitude™ Style Number: PLWD Color: 3606 Chamois Oak Specs: 6″ x 48″ Plank

CHOICE HOTELS COMFORT INN / SUN SCHEME





Manufacturer: Address:

Phone: Contact:

Web:

Dalton, GA 30721 706.277.3000 Amber Osiecki Amber.Osiecki@tarkett.com tarketthospitality.com

Tarkett Hospitality

Product Type: Resilient Wall Base Guest Room

Product Type: Resilient Wall Base

Product Type: Resilient Wall Base

Public Space, Corridor

Public Space, Lobby

Choice Item: SUN-RB-001

Choice Item: SUN-RB-002 Millwork Reveal Wall Base

Style Number: MW-TA5-F

Color: TA5 Colonial Grey Specs: .25" W x 4.25" H x 8' L

Choice Item: SUN-RB-003 Millwork Reveal Wall Base Style Number: MW-121-F Color: 121 Cement

Specs: .25" W x 4.25" H x 8' L

285 Kraft Drive

Choose Tarkett Hospitality

- + Approved Styles
- + Lowest Pricing + Fast Delivery
- + 10-Year Warranty
- + Broadloom Carpet
- + Lextron Solution-Dyed Nylon











Product Type: Resilient Wall Base Fitness Choice Item: SUN-RB-004 Millwork Reveal Wall Base Style Number: MW-199-F Color: 199 Dockside Specs: .25" W x 4.25" H x 8' L





Guest Room Choice Item: SUN-TH-001 Thresholds Style Number: VT-32-M2 Color: 32 Pebble Specs: 5.5" W x 3' L

Product Type: Threshold Public Space Choice Item: SUN-TH-004 Thresholds Style Number: VT-32-M2 Color: 32 Pebble Specs: 5.5" W x 3' L

Product Type: Threshold

O Tarkett Hospitality

SUN SCHEME BROADLOOM / GUEST ROOM






Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Description:	Guest Room
1	
Choice Item:	SUN-CPT-001C
Style Number:	I340B Broadloom
Color:	238
Width:	12'
Repeat:	48" x 48"
Туре:	Dynamics - Multi Level Loop Servo Scroll Tip Shear
Content:	Lextron Enviro-Green Solution Dyed Nylon
Weight:	32 oz. tufted face weight
Primary Backing:	Woven Polypropylene
Secondary Backing:	Action Bac
Pile Height:	.250" High, .187" Med, .062" Low
Gauge:	1/10"
Dye Method:	Solution Dyed
Installation Method:	Broadloom
Flame Requirements:	Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- All Specifications subject to normal manufacturing tolerance.



SUN SCHEME CARPET TILE / GUEST ROOM






Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Description: Choice Item:	Guest Room SUN-CPT-002C
Style Number:	I335T Carpet Tile
Color:	428
Carpet Tile Size:	24" × 24"
Туре:	Dynamics – Servo-Scroll Loop Tip Shear
Content:	Lextron Enviro-Green Solution Dyed Nylon
Weight:	28 oz. tufted face weight
Primary Backing:	Woven Polypropylene
Secondary Backing:	Ethos® Modular w/Omnicoat Technology
Pile Height:	.337" High, .218" 1Med, .187" 2Med, .103" Low
Gauge:	1/10"
Dye Method:	Solution Dyed
Installation Method:	Quarter Turn
Flame Requirements:	Meets or exceeds requirement Class 1

- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104/CRI-105.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- All Specifications subject to normal manufacturing tolerance.



SUN SCHEME BROADLOOM / CORRIDOR





Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Description:	
Choice Item: Style Number:	SUN-CPT-010C 10936 Broadloom
Color:	992
Width:	12'
Repeat:	72" x 60" Side Match
Туре:	Dynamics – Servo-Scroll Loop Tip Shear
Content:	Lextron Enviro-Green Solution Dyed Nylon
Weight:	36 oz. tufted face weight
Primary Backing:	Woven Polypropylene
Secondary Backing:	Unitary Action Bac
Pile Height:	.250" High, .187" Med, .062" Low
Gauge:	1/10"
Dye Method:	Solution Dyed
Installation Method:	Broadloom
Flame Requirements:	Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- All Specifications subject to normal manufacturing tolerance.



SUN SCHEME BROADLOOM / BOH





Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Description:	вон
Choice Item:	SUN-CPT-021
Style Number:	I334B Broadloom
Color:	792
Width:	12' or 15'
Repeat:	36" x 36"
Туре:	Dynamics - Multi Level Loop Servo Scroll Tip Shear
Content:	Lextron Enviro-Green Solution Dyed Nylon
Weight:	32 oz. tufted face weight
Primary Backing:	Woven Polypropylene
Secondary Backing:	Action Bac
Pile Height:	.250" High, .187" Med, .062" Low
Gauge:	1/10"
Dye Method:	Solution Dyed
Installation Method:	Broadloom
Flame Requirements:	Meets or exceeds requirement Class 1

- Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.
- Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.
- Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.
- All Specifications subject to normal manufacturing tolerance.



SUN SCHEME





Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Choice Item:	Standard	Tarl SUN
Classification:	ASTM 1700	Clas
olassification.	AGTIMITIOU	(Sol
Size:		(001 7" x
Total Thickness:	ASTM F386	0.19
Wear Layer Thickness:	ASTM F410	20 r
Accoustical Backing:		0.03
Installation Method:		Unio
Pattern:		Pro
Pattern Type:		Woo
Color:		270
Format Type:		Plar
Edge Treatment:		Mic
Flexibility:	ASTM F137	Pas
Chemical Resistance:	ASTM F925	Pas
Static Load Limit:	ASTM F970	250
Heat Stability:	ASTM F1514	ΔE :
Light Stability:	ASTM F1515	ΔE :
Slip resistance:	ASTM D2047	SCC
Squareness:	ASTM F2055	Pas
Flammability:	ASTM E648	Clas
Residual Indentation:	ASTM F1914	Pas
Impact Sound:	ASTM E2179	ΔIIC
IIC Impact Sound		
Reduction Rating:		68
Commercial Warranty:		15-у

rkett Value N-LVT-001C ass III, Type B olid Vinyl Floor) (60" 97" (5 mm) mil (0.51mm) 39" (1mm) IXPE iclic® oGen™ bod 0266024 West Oak Drift nk crobeveled SS sses 0 psi, ≤ 0.005" ≤ 8.0 ≤ 8.0 OF ≥ 0.5 SS ass 1 ($\geq 0.45 \text{ W/cm}^2$) SS C ≥ 21 dB

68 15-year limited (Light)



SUN SCHEME





Manufacturer:	Tarkett Hospitality
Address:	285 Kraft Drive
	Dalton, GA 30721
Phone:	706.277.3000
Contact:	Amber Osiecki
	Amber.Osiecki@tarkett.com
Web:	tarketthospitality.com

Standard	Tar
ASTM 1700	SUI Cla
	(So
	Tec
	6" ×
ASTM F386	0.1
ASTM F410	20
	Glu
	id L
	Wo
	360
	Pla
	Pas
	Pas
	250
	ΔE
	ΔE
	SC
	Pas
	Cla
AS1M F1914	Pas
	20-
	ASTM 1700 ASTM F386

rkett Value JN-LVT-002C ass III, Type B olid Vinyl Floor) echtonic® x 48" 120" (3.05 mm) mil (0.51mm) ue-Down Latitude™ ood 606 Chamois Oak ank ass asses 50 psi, ≤ 0.005" 5≤8.0 ≦ ≤ 8.0 COF ≥ 0.5 ass ass 1 (\geq 0.45 W/cm²) ass)-year limited

*TECHTONIC® PROTECTION



Broadloom / Corridor SUN-CPT-010C 

Tarkett Hospitality

285 Kraft Drive Dalton, GA 30721 800.871.3211 www.tarketthospitality.com