

Fluctuate Tile

Style Number	SG001
Product Type	Dynamics Tile
Construction	Multi-Level Cut/Loop
Fiber	CF Lextron Enviro-Green
Dye Method	Nylon 100 % Solution Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	Ethos with Omnicat Backing

Specifications

Size Options	9" x 36" / 18" x 36" / 24" x 24"
Gauge	1/10
Stitches per Inch	10
Tufted Weight	22 oz per sq/yd
Total Weight	100 oz
Finished Pile Thickness	.239"
Total Thickness	.331"

Performance

Traffic Class (TARR)	Heavy
Pill Test	Pass
Radiant Panel	Class I
Flammability	ASTM E 648 Class I
Smoke Density	ASTM E 662 Less than 450
LEED Info	Green Label Plus Certified - GLP8320

Warranty	10 Year Limited Warranty
-----------------	---------------------------------

Recommended Install Methods

<u>24x24</u> Ashlar, Random, 1/4 Turn	<u>18x36 / 9x36</u> Ashlar, Herringbone, Basketweave, Half Basket, Boxed In, Stagger
--	---

Enviro-Green yarn has 10% pre-consumer recycled content.
Recommended for moderate (guestroom) carpet traffic levels.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104/CRI-105.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction.

IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

Product Notes

1. Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
2. U.S. Patent numbers: 4,849,267; 6,406,574, US 9,988,760 B2
3. Chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.