

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: : Resilient Vinyl Stair Nosings

1.1. Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.2. Proprietary Product Description:

1.2.1. **Construction:** Tarkett Vinyl Stair Nosings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants to meet the performance requirements of ASTM F-2169 Standard Specification for Resilient Stair Treads, Type TV, Class 1 and 2, Group 1 and 2. Tarkett Vinyl Stair Nosings are available with a 2" (5.08 cm) wide co-extruded strip of contrasting color. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Vinyl Stair Nosings are designed for interior applications only and not recommended for commercial kitchen environments.

1.2.2. Styles:

Visually Impaired

- **VIRCN-XX-A** Visually Impaired Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration, 3-1/8" (7.94 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet, for solid color without co-extruded color strip specify **SRCN-A**
- **VIRCN-XX-B** Visually Impaired Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration, 3" (7.62 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/8" (3.17 mm) resilient or 3/16" (4.76 mm) butt with lip removed, for 2" contrasting color grit strip specify **VIRCN-B2**, for solid color without co-extruded color strip specify **SRCN-B**
- **VITSN-XX-** Visually Impaired Top Set Vinyl Stair Nosing 2" (5.08 cm) square nose configuration, 3" (7.62 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, top-setting on concrete, steel, and wood steps to enhance visibility
- **VIVCD-XX** Visually Impaired Double Undercut Carpet Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration 3-3/16" (8.10 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet on step and riser, for solid color without co-extruded color strip specify **SVCD**

Non-visually Impaired

- **DTN-XX** Top Set Vinyl Stair Nosings for residential use, 1-3/4" (4.45 cm) square nose with 1-3/4" (4.45 cm) tread depth
- **VCD-XX** Double Undercut Carpet Vinyl Stair Nosing, 1-5/16" (2.85 cm) tread depth, 1-9/16" (3.10 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet on step and riser
- **RCN-XX-A** Undercut Carpet Vinyl Stair Nosing, 1-15/16" (4.92 cm) tread depth, 2" (5.08 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet
- **RCN-XX-B** Recessed Vinyl Stair Nosing, 3" (7.62 cm) tread depth with ribbed surface, 2" (5.08 cm) hinged, square nose configuration, undercut for 1/8" (3.18 mm) material
- **SVCD-XX-A** Double Undercut Carpet Vinyl Stair Nosing, 3-1/8" (7.93 cm) tread depth, 1-1/2" (3.81 cm) hinged square nose configuration, undercut for 3/8" (9.53 mm) carpet on step and riser
- **SRCN-XX-C** Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged, square nose configuration, 3-1/8" (7.94 cm) tread depth, undercut for 3/8" (9.53 mm) carpet on step
- **VDL-XX-SQ** 2-1/16" (5.24 cm) treads depth, 2" (5.08 cm) hinged square nose configuration, butt edge for 1/8" (3.17 cm) resilient materials
- **VDL-XX-RD** 1-1/2" (3.75 cm) diameter round nose configuration, 2-1/16" (5.24 cm) tread depth, butt edge for 1/8" (3.17 cm) resilient materials

1.2.3. Physical Characteristics:

Lengths: 12 ft. (3.66 m), Packaging: 120 ft. (39.58 m) per carton, except VI and SRCN-A 72 ft. (21.95 m); VI and SVCD 60 ft (18.29 m); SVCD-A and SRCN-C 48 ft. (14.6 m)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 2.2. **Abrasion Resistance** (ASTM D 3389): < 1 gram weight loss
- 2.3. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .6 for flat surfaces
- 2.4. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com

3. INSTALLATION

3.1. See Stair Tread, Nosing, Riser, and Stringer installation instructions for complete details.

3.2. Adhesives:

- **Tarkett 946 Premium Contact Adhesive Coverage:**
Non-porous Substrate:
1 quart unit (0.95 liters) – 24 to 36 sq. ft.
1 gallon unit (3.79 liters) – 144 to 215 sq. ft.
- **Tarkett 930 Two-part Epoxy Nose Caulk Coverage:**
13.5 oz. cartridge, with #530 Caulking Gun at a ¼" diameter bead – approximately 50 linear feet.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to vinyl nosing maintenance instructions for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com