

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** QuietHour Acoustic flooring is ortho-phthalate free, luxury vinyl tile with attached acoustic pad, suitable for light commercial environments.


1.2. Manufacturer:

Tarkett Hospitality
285 Kraft Dr..
Dalton, GA 30721
Web: www.tarketthospitality.com

Phone: (800)-871-3211

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett QuietHour is an Ortho-Phthalate-Free, 100% virgin material luxury vinyl constructed with an IXPE acoustical backing.



1.3.2. Characteristics:

- **Edge treatment:** Micro-Bevel
- **Overall thickness:** 0.197" (5 mm)
- **Wearlayer Thickness:** .020" (0.5 mm)
- **Core Thickness:** 0.157" (4 mm)
- **Acoustic Backing:** 0.039" (1 mm) IXPE
- **Installation System:** Glue down

1.3.3. Tile/Plank size and Packaging:

- **7" x 48" (17.78 cm x 121.92 cm)**
12 planks per box, 28 ft² (2.6 m²), 43.25 lbs. (19.62 kg),
50 boxes per pallet

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Meets ASTM F1700, Class III, Type B performance

2.2. **Dimensional Stability** (ASTM F2199): Passes

2.3. **Indentation Recovery** (ASTM F1914): Passes

2.4. **Heat Stability** (ASTM F1514): $\Delta\sum \leq 8$

2.5. **Light Stability** (ASTM F1515): $\Delta\sum \leq 8$

2.6. Sound Transmission:

	(ASTM E492) 6" slab with drop ceiling	(ASTM E2179)
QuietHour	IIC 64	Δ IIC 23

2.7. **Chemical Resistance** (ASTM F925): Passes

2.8. **CAN/ULC S102.2:** FSR 125 / SDC 340

2.9. Fire Performance:

- **Critical Radiant Flux** (ASTM E648): Class 1 ($> 0.45 \text{ W/cm}^2$)
- **Smoke Development** (ASTM E662): <450

3. INSTALLATION

See QuietHour installation instructions for complete details.

3.1. Adhesives:

- **Tarkett 999HM High Moisture Adhesive**
Porous Substrates: 125-150 sq. ft. per gallon
Non-Porous Substrates: 250-300 sq. ft. per gallon

4. AVAILABILITY AND COST

Available direct through Tarkett Sales Representatives.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Even Plane Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarketthospitality.com

Contact Technical support at (800)-871-3211

7. WARRANTY

Limited 15-year Light Commercial warranty. For complete details, contact Tarkett.