

RIGID CORE FLOORING

Rigid. Flexible. Beautiful.



Rigid construction. Flexible design.

NuGen luxury vinyl flooring offers the best of both worlds: the enhanced performance of rigid core strength, with a suite of flexible designs for today's most frequented hotels..

No wrong answers.

0

Available only in our bestselling designs, NuGen simplifies the renovation process with fashion-forward style and easy installation, so there's never a wrong selection. Each pattern combines the authentic look of wood grain with waterproof performance to stand up to the daily demands of hospitality environments. Perfect for guest rooms, fitness rooms and employee break areas, NuGen delivers beauty, value and performance.

> DRIFTWOOD | SAND CLICK SYSTEM: 270285009 GLUE DOWN: 270286009

CHESTNUT RIDGE | FURROWED CLICK SYSTEM: 270285005 GLUE DOWN: 270286005

NuGen[™]

MINERAL OAK | LONG GRAIN CLICK SYSTEM: 270285004 GLUE DOWN: 270286004

> PECAN FLAME | CLARO CLICK SYSTEM: 270285006 GLUE DOWN: 270286006

A total solution.

Tough enough to stand up to the rigors of daily wear and maintenance, yet beautiful and comfortable underfoot to welcome guests from the moment they walk in the door, NuGen gives you the best of both worlds. With easy, no-mess installation, guaranteed long-term wear and authentic-looking wood designs, NuGen is an ideal choice for the building project and the property.



NuGen[™]

Choose from 10 classic wood designs to complement any decor.

Teak Marado

Click System: 270285001

Glue Down: 270286001

Natural

Furrowed



Wessex Rail Ligna Click System: 270285000 Glue Down: 270286000



Mineral Oak Long Grain Click System: 270285004 Glue Down: 270286004



Alsace Oak Limed Natural Click System: 270285008 Glue Down: 270286008





WATERPROOF













Sparrow Oak Gray Pearl Click System: 270285002 Glue Down: 270286002



Pecan Flame Click System: 270285006 Glue Down: 270286006

Accessories







Milled Oak Sun Toned Click System: 270285003 Glue Down: 270286003



Cottage Plank Bella Click System: 270285007 Glue Down: 270286007

T-Molding

Ensures a smooth transition between flooring at the same height.

Universal Reducer

Makes an attractive and safe transition between flooring of different heights.

> CHESTNUT RIDGE | FURROWED CLICK SYSTEM: 270285005 GLUE DOWN: 270286005

7" x 48'

Driftwood Sand Click System: 270285009 Glue Down: 270286009





7" x 48"

7" x 48"





Doing Good— Together.

At Tarkett North America, we believe that together, we can make a positive impact on people and the planet. That's why we're Doing Good—Together, connecting our sustainability efforts with what our customers value and our world needs. It's an active, living commitment to create a future where people and the planet prosper in balance. Where sustainable flooring solutions don't just perform, they inspire.

NuGen is 100% post consumer recyclable right back into new LVT products.

All over the world, the Tarkett ReStart® program helps customers manage their flooring waste from job installations, collecting off-cut or used vinyl materials.

Plus, Tarkett is implementing cost-effective local take-back programs, and designing our flooring systems to be easily uninstalled and disassembled for cost-effective sorting and recycling.



DESIGNING FOR LIFE Developing products based on

Cradle to Cradle® principles that contribute to people friendly spaces AND respect the planet's natural capital.



CLOSING THE LOOP

Building a circular economy inclusive of programs and business models that encourage take back, reuse, recycling and elimination of waste



DRIVING COLLABORATION

Inviting others to join us in Doing Good through education, collaboration, transparency and communication



Maria Vice Adres & Provinse

NuGen[™]

SPECIFICATIONS	
Nominal Thickness	Click System: 0.177" (4.5 mm) Glue Down: 0.138" (3.5 mm)
Wear Layer Thickness	0.012" (0.3 mm)
Click Only IXPE Acoustical Backing	1 mm
Finish Edge	Square
Finish	Polyurethane
Material	Phthalate Free, 100% Virgin Material
Reusable Content	100% Reclaimable
Scratch/Scuff/Abrasion Properties	Excellent
Dimensional Stability	ASTM F2199 Passes
Static Load Limit	ASTM F970 Passes
Residual Indentation	ASTM F1914 Passes (PSI Equivalent > 5,000 lbs.)
Slip Resistance	ASTM D2047 ≥ 0.5 SCOF
Fire	ASTM E648 ≥ .45 w/cm ²
Smoke	ASTM E662 ≤ 450
Heat Stability	ASTM F1514 ∆ E ≤ 8
Light Stability	ASTM F1515 ∆ E ≤ 8
Staining	ASTM F925 Passes
Installation System	Click System: UniClic Locking System Glue Down: Adhesive
FloorScore [®] Certification	Certified
Size	Click System: 7.13" x 48.03" (181mm x 1220mm) Glue Down: 7.32" x 48.03" (186 mm x 1220 mm)
Pieces per Carton	Click System: 12 Planks Glue Down: 12 Planks
Weight per Carton	Click System: 39.47 lbs. (17.9 kgs.) Glue Down: 39.93 lbs. (18.1 kgs.)
Area per Carton	Click System: 28.52 sq. ft. (2.65 m²) Glue Down: 29.31 sq. ft. (2.72 m²)
Cartons per Pallet	Click System: 55 Glue Down: 55





For more accurate color and pattern representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample.

Tarkett North America

30000 Aurora Road Solon, OH 44139 USA: 800-871-3211

www.tarkettna.com

ON THE FRONT COVER: TEAK MARADO | NATURAL | CLICK SYSTEM: 270285001 | GLUE DOWN: 270286001

> ©Tarkett USA Inc. 10/2019 Printed in USA NUG01 2019B BR BROCHR