



# The beauty of better engineering.

With ProGen™ luxury vinyl flooring, what you see is only the beginning of what you get. Discover better engineering in every detail—like heavy-duty resistance to high heels and rolling luggage, waterproof installation, and incredible

comfort underfoot. But our favorite part of ProGen is its quiet disposition— with an IIC rating of 68 that lets you welcome guests with tranquil escape. Next stop: Dreamland.





WATERDROOF





EASY TO INSTAI





# **Thermal Stability**

ProGen is designed to handle wide temperature fluctuations from windows and sunlight.

## **Easy Installation**

Its easy Uniclic® system is faster than traditional installation systems, saving you time and money.

#### Durable

Resists the stresses of modern day hospitality environments, from heavy rolling suitcases to high heels and heavy furniture.

## Waterproof

Safe to use in guestrooms, kitchenettes and bathrooms.

### **Rigid Core**

Overcomes subfloor imperfections, unlike traditional luxury vinyl tile.

#### Quiet

IIC rating of 68 means superior sound absorption to drastically improve overall comfort.

ProGen™ is a radical leap forward in flooring technology—a rigid core construction engineered from the inside, out—and designed to outperform the extreme demands of today's hospitality environments. ProGen beautifully resists heavy rolling luggage, high heels and heavy furniture, plus a variety of unavoidable mishaps like splashes and spills. ProGen can be installed virtually anywhere, without being affected by heavy sunlight or extreme temperature changes, so it resists buckling, denting and warping. With beautiful, authentic-looking designs, an easy, nomess installation, and guaranteed long-term wear, ProGen promises a better experience every step of the way.



## Installation

Floating Floor	Quick and Simple Angle-Angle Click		
Above/At/ Below Grade	<b>✓</b>		
No Acclimation	<b>✓</b>		
3-Seasons Room	<b>✓</b>		
No Temperature Limitations	<b>✓</b>		
Acoustic Rating	Total IIC of 68 (6" Concrete Slab + Suspended Ceiling)		

## **New, Trend-Setting Designs**

Make your design visions a reality through a variety of on-trend designs.




**Realistic Embossing** 




**Modern Painted Bevels** 



# **Dimensional Stability and Durability**



Contraction and Expansion in Mils (ASTM F2199)



Residual Indentation (ASTM F1914 0.178" @ 140 lbs.)



Durham Pine | Sun-Toned 270264014



Rock Maple | Medio 270264012



Stained Maple | Carmine 270264015



Cerused Oak | Powder 270265013



Tannin Walnut | Gris 270265016



Aurora Oak | Starry Night 270265020



Red Oak | Ginger 270264016



Durham Pine | Tavern 270264013



Vista Oak | Limed Natural 270265015



Stokes Range | Relic 270265018



Cerused Oak | Denim 270265014



Brushed Pine | Sorrel 270265019



Stokes Range | Dusk 270265017



West Oak | Drift 270266024



Spicebark Hickory | Fumed 270266016



Spicebark Hickory | Comino 270266017



North Shore Pine | Cascade 270266020



Milled Oak | Copper 270266018



West Oak | Loft 270266022



West Oak | Natural 270266021



Pacific Madrone | Natural 270266019



West Oak | Mountane 270266023





SPECIFICATIONS				
Total Thickness	5 mm			
ProGen Core <sup>®</sup> Technology	4 mm			
Acoustical Backing Layer	1 mm			
Wear Layer Thickness	20 mil	20 mil		
Material	Phthalate Free, 100% Virgin Material			
Reusable Content	100% Reclaimable			
Plank Size	5" x 48"	7" x 48"	7" x 60"	
Sq. Ft. per Carton	26.68 sq. ft.	28.52 sq. ft.	29.61 sq. ft.	
Planks per Carton	16	12	10	
Cartons per Pallet	56	50	40	
Lbs. per Carton	42 lbs.	44 lbs.	45 lbs.	
ASTM F2199 (Dimensional Stability)	Passes			
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)			
ASTM F1514 (Heat Stability)	Passes			
ASTM F1515 (Light Stability)	Passes			
ASTM E2179 (Impact Sound Reductions)	Δ IIC ≥ 20 dB			
IIC Impact Sound Reduction Rating	68			
ASTM F925 (Resistance to Chemicals)	Passes			
ASTM D5116 (VOC Requirements)	Passes < 0.1 mg/m³			
Scratch/Scuff/Abrasion Properties	Excellent			
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles			
Installation System	Uniclic®			
Certification	FloorScore® Certification			
Residential Warranty	Lifetime			
Light Commercial Warranty	15-Year			
3-Seasons Warranty	10-Year			



# **Tarkett North America**

30000 Aurora Road Solon, OH 44139 USA: 800-871-3211 ON THE FRONT COVER: VISTA OAK | LIMED NATURAL | 270265015

©Tarkett USA Inc. 09/2019 Printed in USA PR001