

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
<b>Classification</b>	-	Rubber Floor Tile (ASTM F1344)
<b>Total thickness</b>	ASTM F386	0.125 " (3.18 mm)
<b>Installation method</b>	-	Glue-Down
<b>Pattern</b>	-	Solid
<b>Chemical Resistance</b>	ASTM F925	Good
<b>Static Load Limit</b>	ASTM F970	Pass
<b>Heat stability</b>	ASTM F1514	$\Delta E \leq 8.0$
<b>Slip resistance</b>	ASTM D2047	SCOF $\geq 0.6$
<b>Flammability</b>	ASTM E648	Class 1 ( $\geq 0.45$ W/cm <sup>2</sup> )
<b>Smoke Density</b>	ASTM E662	< 450
<b>Hardness</b>	ASTM D2240	Not Less than 85 Shore A

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
<b>Cradle-to-Cradle</b>	-	Bronze
<b>ReStart®</b>	-	Yes
<b>TVOC emission</b>	-	$\leq 500 \mu\text{g} / \text{m}^3$
<b>Floorscore certified</b>	-	Yes