



**103L MOD IV
PRODUCT SPECIFICATIONS**

| | |
|---------------------------|-----------------------------------------------------------|
| Style | 103L Mod IV |
| Construction | Legacy Cut Pile |
| Fiber | 100% C.F. Lextron Enviro-Green Solution Dyed Nylon |
| Pitch | 189 |
| Tufted Pile Weight | 36 oz. Per Sq. Yard |
| Pile Height | .250" |
| Row | 12 |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Unitary with Action Bac |
| Dye | Solution Dyed |
| Total Weight | 72 oz. |
| Width | 15 ft. |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 |
| Pattern Repeat | 45 in. W x 60 in. L |
| Warranty | 10 Year Wear Guarantee |
| Traffic Class | Heavy (Corridor/Public Areas) |

Enviro-Green yarn has 10% pre-consumer recycled content. 

Recommended for heavy (corridor/public area) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.