

**IN147 DIVERGENCE IV
PRODUCT SPECIFICATIONS**

| | |
|--------------------------|---|
| Style | IN147 Divergence IV |
| Construction | Intrepid Multi-Level Loop Tip Shear |
| Fiber | 100% C.F. Lextron Enviro-Green Solution Dyed Nylon |
| Gauge | 1/10 |
| | 42 oz. Per Sq. Yard |
| Pile Height | .250" High - .062" Low |
| Stitches Per Inch | 28 |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Unitary Action Bac |
| Dye | Solution Dyed |
| Total Weight | 78 oz. |
| Width | 12 ft. |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 |
| Pattern Repeat | 36 in. W x 57 in. L |
| Warranty | 10 Year Wear Guarantee |
| Traffic Class | Heavy (Public Space) |

Enviro-Green yarn has 10% pre-consumer recycled content. 

Recommended for heavy (public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.