



Saveur #11442

Product Specification

| Face Construction | Imperial | Metric |
|-------------------------------|--|------------------|
| Construction | Stratatec® Patterned Loop | |
| Gauge | 5/64 | 50.4 rows/10 cm |
| Stitches per Inch | 9.6 | 37.8 pu/10 cm |
| Tuft Density | 122.88 tufts/sq in | 19.0 tufts/sq cm |
| Pile Height Average | 0.141 inch | 3.6 mm |
| Pile Thickness | 0.044 inch | 1.1 mm |
| Density Factor | 9,818 oz/cu yd | 363.3 kg/cu m |
| Fiber System | Dynex SD® Nylon (Permanent Stain Resistance) | |
| Dye Method | 100% Solution Dyed | |
| Fluorine-Free Soil Protection | Eco-Ensure | 7.6 Kilotex |
| Primary Tufting Substrate | Synthetic Non-Woven | |
| Pattern Match | Not required | |

Third Party Environmental Certifications

| Product | Recycled Content* | | NSF 140 | Cradle to Cradle |
|--|-------------------|--------------|---------------|-------------------|
| | Overall | Postconsumer | SCS Certified | Certified™ v3.1** |
| Certified ER3® Modular | 45-66% | 14% | Gold | |
| Certified ethos® Modular with Omnicoat Technology™ | 47-75% | 28% | Platinum | Silver |
| Certified Flex-Aire Modular® Cushion | 21-41% | 4% | Gold | |

*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

**Cradle to Cradle Certified is a certification mark licensed by the Cradle to Cradle Products Innovation Institute

Product Testing/Information

| | |
|--------------------------|--|
| Antimicrobial Chemicals | No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05) |
| Electrostatic Propensity | <3.0 kV (AATCC 134); Permanent Conductive Fiber |
| Surface Flammability | Passes CPSC FF 1-70 (ASTM D-2859) |
| Flooring Radiant Panel | Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648) |
| Smoke Generation | Less than 450 (ASTM E-662) |
| Colorfastness to Light | ≥ 4 after 100 hours (AATCC 16E) |
| Soil Protection | Application Rate: 2% of Face Weight |
| Stain Resistance | ≥ 8 (AATCC 175-08 Stain Resistance Pile Floor Coverings) |

Installation Methods

| | |
|---------------------|---|
| Peel and Stick | RS Adhesive System - Full Coverage Peel & Stick |
| Wet Spread | Backing specific Tandus Adhesives |
| Installation Method | Vertical Ashlar; 18" x 36", 9" x 36" Vertical Ashlar, Herringbone |

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,297; 4,849,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574
- The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Tarkett North America

Technical Services Department
 1000 Vista Drive
 Dalton, GA 30721
 800.248.2878 Fax 706.259.2136
 info@tarkettna.com

www.tarkettna.com

© 2019 Tarkett USA Inc. 01/2019

Modular Options

IMPERIAL

METRIC

TEST METHOD

Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering & backing resiliency loss. Lifetime limited stain resistance.

ER3® Modular

| | | | | | | |
|------------------------------------|--|-----------|----------------|------|---------|----------------------------|
| Total Minimum Recycled Content | 56.2% | | | | | SCS Certified total 45-66% |
| Pre-Consumer | 38.7% | | | | | SCS Certified |
| Postconsumer | 17.5% | | | | | SCS Certified |
| Third Party Certification NSF-140 | Gold | | | | | SCS Certified |
| Product Size | 24" x 24" Tile (9" x 36" and 18" x 36" also available) | | | | | |
| Secondary Backing | 100% Recycled Content with Tru Bloc (Barrier System) | | | | | |
| Intermediate Layer | Fiberglass Reinforced Sealant | | | | | |
| Product Construction | No Delamination per ASTM D-3936 | | | | | |
| Secondary Backing Density | 65 | lbs/cu ft | | 1041 | kg/cu m | |
| Secondary Backing Thickness | 0.087 | inch | | 2.2 | mm | |
| Total Weight with RS / Non-RS | 122.5 | 120.9 | oz/sq yd +/-5% | 4154 | 4100 | g/sq m |
| CRI Green Label Plus Certification | GLP1366 | | | | | |

ethos® Modular with Omnicoat Technology™

| | | | | | | |
|------------------------------------|--|-----------|----------------|--------|---------|----------------------------|
| Total Minimum Recycled Content | 62.0% | | | | | SCS Certified total 47-75% |
| Pre-Consumer | 25.2% | | | | | SCS Certified |
| Postconsumer | 36.8% | | | | | SCS Certified |
| Third Party Certification NSF-140 | Platinum | | | | | SCS Certified |
| Cradle to Cradle Certification | Silver (Certification #1904) | | | | | |
| Product Size | 24" x 24" Tile (9" x 36" and 18" x 36" also available) | | | | | |
| Secondary Backing | 50% Recycled Content | | | | | |
| Intermediate Layer | Fiberglass Reinforced Sealant | | | | | |
| Product Construction | No Delamination per ASTM D-3936 | | | | | |
| Secondary Backing Density | 65.0 | lbs/cu ft | | 1041 | kg/cu m | |
| Secondary Backing Thickness | 0.050 | inch | | 1.3 | mm | |
| Total Weight | 89.9 | | oz/sq yd +/-5% | 3047.3 | g/sq m | |
| CRI Green Label Plus Certification | GLP8320 | | | | | |



Flex-Aire Modular® Cushion

| | | | | | | |
|------------------------------------|--|--------------------------|----------------|------|---------|----------------------------|
| Total Minimum Recycled Content | 26.6% | | | | | SCS Certified total 21-41% |
| Pre-Consumer | 20.6% | | | | | SCS Certified |
| Postconsumer | 6.0% | | | | | SCS Certified |
| Third Party Certification NSF-140 | Gold | | | | | SCS Certified |
| Product Size | 24" x 24" Tile (9" x 36" and 18" x 36" also available) | | | | | |
| Secondary Backing | Fiberglass Reinforced Composite Closed Cell Cushion | | | | | |
| Intermediate Layer | Fiberglass Reinforced Sealant | | | | | |
| Product Construction | No Delamination per ASTM D-3936 | | | | | |
| Cushion Weight | 35.5 | oz/sq yd | | 1203 | g/sq m | ASTM D-3574 |
| Cushion Density | 18.5 | lbs/cu ft | | 296 | kg/cu m | ASTM D-3574 |
| Cushion Thickness | 0.156 | inch | | 4.0 | mm | ASTM D-3574 |
| Total Weight with RS / Non-RS | 111.1 | 109.7 | oz/sq yd +/-5% | 3768 | 3720 | g/sq m |
| Compression Set | Max. 10% | | | | | |
| Compression Deflection | 5 Min. | 25 max lbs/sq inch @ 25% | 352 | 1758 | g/sq cm | ASTM D-3574 |
| CRI Green Label Plus Certification | GLP6558 | | | | | |