



## **W0080 Nowhaus**

Product Type	Broadloom
Style Number	W0080
Construction	Prestige - Pattern Cut
Fiber	Lextron Enviro-Green Nylon
Dye Method	100 % Solution Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	Unitary

### **Specifications**

Size	12'
Gauge	1/10
Stitches per Inch	10
Tufted Weight	36 oz per sq/yd
Total Weight	80.0 oz
Density	3,293
Finished Pile Thickness	.41 inches
Pattern Repeat	144" x 151.20"
Overall Thickness	.391 inches

### **Performance**

Traffic Class (TARR)	Heavy
Pill Test	Pass
Radiant Panel	Class I
Flammability	ASTM E 648 Class I
Smoke Density	ASTM E 662 Less than 450
LEED Info	Green Label Plus Certified – GLP8320

<b>Warranty</b>	<b>10 Year Limited Warranty</b>
-----------------	---------------------------------

### **Available Customs**

Backings	
Tiles Sizes	13' 6" and 15'

Enviro-Green yarn has 10% pre-consumer recycled content. 

Recommended for heavy (public space) carpet traffic levels.

**NOTE:** Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104.  
Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction.

IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.