Tarkett Hospitality

W0112 Blot

Product Type	**Broadloom**
Style Number	**W0112**
Construction	**Vivid - Pattern Cut/Loop**
Fiber	**Lextron Enviro-Green Nylon**
Dye Method	**100 % Solution Dyed**
Primary Backing Secondary	**Woven Polypropylene**
Backing	**Unitary**

Specifications

Size	**12'**
Gauge	**1/11**
Stitches per Inch	**11.5**
Tufted Weight	**42 oz per sq/yd**
Total Weight	**79.8 oz**
Density	**4,974**
Finished Pile Thickness	**.283 inches**
Pattern Repeat	**72" x 87.27"**
Overall Thickness	**.451 inches**

Performance

Traffic Class (TARR)	**Heavy**
Pill Test	**Pass**
Radiant Panel	**Class I**
Flammability	**ASTM E 648 Class I**
Smoke Density	**ASTM E 662 Less than 450**
LEED Info	**Green Label Plus Certified – GLP2380**
Warranty	**10 Year Limited Warranty**

Available Customs

Backings	
Sizes	**13' 6" and 15'**

Enviro-Green yarn has 10% pre-consumer recycled content.

Recommended for heavy (public space) carpet traffic levels.

NOTE: Due to the manufacturing process of a tip shear product, the finished yarn weight will vary more than normal manufacturing tolerances and side match cannot be guaranteed.

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. IT IS NOT A CARPET DEFECT, but is inherent in solution dyed graphic and cut/loop patterns.

All Specifications subject to normal manufacturing tolerance.